



Logo Placements

1330 High-Vis Shell Jacket Class 3

Recommended logo placements

Heat Seal

- 1 Left breast, 1 cm above yoke seam, maximum size 120x120 mm
- 2 Left sleeve, center between reflective and shoulder seam, maximum size 120x120mm
- 3 Right breast, 1 cm above yoke seam, maximum size 120x40 mm
- 4 Right sleeve, center between reflective and shoulder seam, maximum size 120x120mm
- 6 Back, 2 cm below yoke seam, 280x280 mm
- 23 Right breast, 2 cm below placement 3, maximum size 120x120 mm
- 61 Centered between reflective tape 280x35 mm



Maximum size of logo cm² to keep classification EN 20471

Size	cm ²	cm
XS	20	4x5
S	710	26x26
M-XXXL	1010	31x31

To maintain the Class 3 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.

Embroidery is not possible, there is no zip, so we cannot seal the embroidery and make it water proof.

- 1Y Add Y after the placement and it will be turned from bottom to top
- 1B Add B after the placement and it will be below the (1B)
- 1Z Add Z after the placement and it will be turned from top to bottom

